

# ER2 Electric Chain Hoist Lineup

Type	Lifting speed		Capacity ( t )													
			125kg	250kg	500kg	1	1.5	2	2.5	3	5	Large capacity				
												7.5	10	15	20	
Hook suspension ER2	Single	Low			•	•		•								
		Standard		•	•	•	•	•	•	•	•		•	•	•	
		High	•	•												
	Dual inverter	Low			•	•		•								
		Standard		•	•	•	•	•	•	•	•					
		High	•	•												
Trolley suspension Motorized trolley ER2M Plain Trolley ER2SP (up to 5t) Geared Trolley ER2SG	Single	Low			•	•		•					•			
		Standard		•	•	•	•	•	•	•	•	•	•	•	•	
		High	•	•												
	Dual inverter	Low			•	•		•								
		Standard		•	•	•	•	•	•	•	•					
		High	•	•												

KITO will not be held liable for any malfunction, lack of performance or accident if the product is being used in conjunction with any other equipment. If the product is to be used for unintended purposes, please confirm with your dealer in advance.

## Trolleys

### Motorized Trolley MR2

Bearing built-in side rollers provide smooth running through the minimum radius curve and excellent traversing performance with preventive derailment.

#### Features

- Simple gear box construction
- Improved balance due to a lighter weight geared motor
- Speed variations
  - Single Low Speed
  - Single Standard Speed
  - Dual Speed

### Plain & Geared Trolley

- Designed to provide smooth and easy traversing.
- Lugs provide protection from striking damage against rail stoppers, and from falling off the rail.
- Wheel flanges also prevent derailment.

### Plain Trolley TSP

Designed for light load manual applications (125kg to 5t)

### Geared Trolley TSG

Designed for precise positioning and traversing by using hand chain (125kg to 20t)

Motorized Trolley MR2



125kg to 20t

Plain Trolley TSP




125kg to 3t




5t

Geared Trolley TSG



125kg to 3t



5t to 20t